



**ALPHACOOOL – THE COOLING COMPANY**



## Alphacool NexXxoS UT60 X-Flow 80 mm Quad

### What is it

A fully copper server radiator that is compatible with 2U server racks. It provides space for 80 mm for-mat fans that can be mounted on one or both sides. The radiator offers three connection options on each side and has holes for M3x5 screws on the top and bottom.

### Highlights

- Compatible with server racks in 2U format
- Solid copper radiator
- Many different connection options
- Patented countersunk screw plugs

Version: 25.03.2019

We assume no responsibility for any typing errors

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: [info@alphacool.com](mailto:info@alphacool.com)

## Scope of delivery

1x Mounting material

## Technical datas

L x W x H	364,5 x 60 x 80 mm
Net weight	1049 g
Max. working temperature	180 °C
Material cooling fins	Copper
Material cooling channels	Copper
Prechambers material	Copper
Material outer housing	Steel
Fins per Inch	10
Threads	6x G1/4"
Mounting options	12 x M3 Threads
Fan size	80 mm
Fan slots	4 single-sided / 8 double-sided
Fan threads	M3
Pressure tested	1,5 Bar
Certifications	CE, FC, ROHS

## Other datas

Article numbers Alphacool	14297
EAN Code	4250197142977
PU	I
Dimensions PU L x W x H	43 x 9,5 x 7,5 cm
Weight	1049 g
Customs code	84195080900

## Product pics download

[https://www.alphacool.com/download/1015725\\_80mm\\_Quad.zip](https://www.alphacool.com/download/1015725_80mm_Quad.zip)

Version: 25.03.2019

We assume no responsibility for any typing errors

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

## Article text

Alphacool is an internationally renowned company in the field of watercooling solutions for both industrial and end customer. Constantly innovating and improving both server and home solutions, Alphacool strives to create the perfect solution.

### Perfect for workstations and servers

The 80 mm NexXxoS radiators are specially designed for server racks and workstations. Due to their low height of only 80 mm and the special M3 mounting holes on the top and bottom, they're perfect for 2U server racks. Alternatively, the radiators can also be mounted in the classic way using the mounting locations of the fans. M3 screws are also required here.

### No compromise on materials

Alphacool always uses copper in its NexXxoS radiators. Alphacool is the only manufacturer that uses pure copper for all water-bearing components. Starting with the end chambers, the water channels and the cooling fins, everything is made of pure copper. Only the connecting threads are made of brass, as pure copper would be too soft for the threads and would give way over time.

### Outstanding cooling capacity

There are several approaches that Alphacool uses to increase the cooling capacity. Using copper ensures the best properties to dissipate the heat. Aluminium, which is often used in low-cost products, is not as good as copper in terms of heat capacity and thermal conductivity.

Compared to some other manufacturers, the copper fins are only thinly painted. This means that the cooling performance isn't affected at all unlike a thick coating of paint which would act as an insulator. The fin spacing is 10 FPI for optimal performance. This means that the fins are close enough together to create a large surface, but also far enough apart not to obstruct the air flow. In addition, all fins are designed to provide controlled air turbulence. This means that the air flowing through the fins is more efficient and is directed exactly where it is needed.

### X-Flow instead of U-Flow

The water flow in classic PC radiators is U-shaped. This means that the water inlet and outlet are on the same side on the radiator. This has certain advantages in the normal PC, however, it is difficult to set up a reasonable cooling loop like this in an extremely flat server. Due to the X-Flow technology, the input and output are located on the opposite sides. This makes it very easy to create a loop in the server rack. For example, you could go out from one side, directly into a CPU, then into one or more graphics cards and the pump, then back to the radiator on the other side.

### Versatile connection options

Each NexXxoS 80 mm X-Flow radiator has 3 ports on each end of the radiator. This means that almost any conceivable mounting position can be achieved. The connections are located on each side in the opposite position and then one at the head ends of the radiators.

Alphacool has developed special patented stop plugs that are flush with the radiator to avoid them fouling the case. Previous solutions always exceeded the length or width of the radiator because they were not countersunk.

If you are interested in a professional implementation of water cooling for your servers or workstations in your data centre, Alphacool also offers complete solutions with special reservoirs, pumps and coolers. These include highly optimized water coolers for workstation graphics cards and CPUs. To find out more about this, send us your request to: [info@alphacool.com](mailto:info@alphacool.com)

Version: 25.03.2019

We assume no responsibility for any typing errors

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: [info@alphacool.com](mailto:info@alphacool.com)