

Alphacool article number: 14353

Aquatuning article number: 1019152

Alphacool offers with the ST25 radiators an extremely flat version of the popular full copper NexXxoS radiators. Thanks to the low thickness of the radiators, they can also be very well accommodated in SFF housings. The use of copper for all water-carrying components and the cooling fins means that the cooling performance is outstanding.

### Alphacool NexXxoS ST25 240mm Radiator



- Copper radiator
- Ultra flat with 25 mm height
- Perfect cooling fins structure
- Safety plates against screwing in too deeply

## Scope of delivery

8 x M3x30mm screws

8 x M3x5 mm screws

8 x M3x35 mm screws

1 x Allen key

## Data radiator

L x W x H	272 x 120 x 25,5 mm (+/- 3%)
FPI	15
Material cooling fins	Copper
Material chambers	Copper
Material cooling channels	Copper
Material threads	Brass
Material outer housing	stainless steel
G 1/4" threads	2 x
For fan size	120 mm
Possible fan assembly	2 x one-sided / 4 x both-sided

## Download links

Product pics	<a href="http://www.alphacool.com/download/1019152_NexXoS_ST25_240mm.zip">http://www.alphacool.com/download/1019152_NexXoS_ST25_240mm.zip</a>
--------------	-----------------------------------------------------------------------------------------------------------------------------------------------

## Packaging dimensions 1 unit

L x B x H	34 x 14 x 4 cm
Weight	0,676 kg

## Other data

Certificates	CE, FC, RoHS
EAN	4250197143530
Customs code	84195080900

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: [info@alphacool.com](mailto:info@alphacool.com)

## Article text

Alphacool is an internationally renowned company in the field of water cooling solutions for both industrial and home users. To ensure that customers receive the best products available, Alphacool is constantly developing new products and making improvements to existing products.

### **Make No Compromises, Use Copper.**

As usual, Alphacool uses pure copper for the NexXoS ST25 slim radiators. The end chambers, the water channels and the cooling fins are all made of copper, a unique selling point worldwide. No other manufacturer relies on pure copper for all these components combined. As a result, Alphacool has been producing one of the most popular and highest performing radiators on the market for many years, providing the perfect foundation for every water cooling system.

### **Full Cooling Capacity**

To maximize the performance of a radiator, Alphacool reaches deep into its bag of tricks. Copper is the starting point. With a thermal conductivity of 400 W/(mK) for copper compared to 236 W/(mK) for aluminium, the winner is clear. Alongside this is the special fin density. Alphacool is one of the oldest companies in the field of water cooling and has carried out countless laboratory tests. The result is a fin spacing of 15 FPI. This means that the air flow is only slightly obstructed as the air can pass through even without high pressure. However, the cooling capacity does not suffer from this, on the contrary. To use the air flow optimally, all cooling fins have small serrations. These are tiny flaps that guide the airflow in the desired direction and increase the surface area. In the case of radiators, they are barely 1 mm high, but still provide controlled air turbulence to increase cooling capacity and minimise airflow noise.

### **Compact**

The ST25 slim radiators offer the ideal liquid cooling solution for Mini-PCs or SSF (Small Form Factor) systems. Due to the extremely flat design, the NexXoS ST25 radiators are ideal for such small cases and due to the reduced size, they give you the extra space you need to work in the case.

### **Safety first**

The NexXoS ST25, like the previous NexXoS radiators, offer special protection that prevents fan or mounting screws from being screwed in too deeply. Protective plates have been placed under all mounting holes which ensure the screws cannot be inserted too far. This protects the underlying cooling fins and water channels.